



RocketLinx® ES7510-XT

Part Number: 32046-3



KEY FEATURES AND BENEFITS

- Integrate IP cameras, access points and other PoE devices
- Supports TACACS+
- Eight 10/100BASE-TX PoE Plus ports and two Gigabit RJ45/SFP combo ports featuring Digital Diagnostic Monitoring (DDM)
- PoE ports support both IEEE 802.3af (15.4W) and the latest high power IEEE 802.3at standards (30W)
- Eco-Friendly Power Budget Efficiency Mode
- Easy setup and administration via Netvision application, web page or Cisco-like command line interfaces
- Advanced redundant ring support with 5ms recovery time, for up to 4 x 100M rings plus two Gigabit uplink rings
- Advanced security features include Port Security, Access IP List, HTTPS and SSH login
- SNMP and IEEE 802.1AB LLDP for network management
- Tag-VLAN supporting multiple VLAN traffic isolation
- LACP port trunking for bandwidth aggregation to support video surveillance
- Redundant DC power inputs and multiple event relay output for advanced device alarm control
- Extended operating temperature -40° to 75°C
- NEMA TS2 certified
- RoHS2 compliant under CE
- IPv6 support

POE SWITCH

PRODUCT DESCRIPTION

PoE Plus Supporting High Power Devices

The Comtrol RocketLinx ES7510-XT managed industrial PoE Plus switch is designed to meet the high power and advanced management needs of critical traffic applications such as real-time IP video surveillance and wireless communication utilizing outdoor rated IP cameras and high power IEEE 802.11 access points. Featuring a rugged design for harsh environments, intuitive web, CLI, SNMP management options, power scheduling and eight fully compliant IEEE 802.3at PoE injector ports, the ES7510-XT is easily installed in industrial settings and traffic cabinets supporting even the most power intensive devices such as IP cameras with heaters and pan/tilt/zoom controls.

Innovative Power Control

In addition to functioning as a PoE power source, the ES7510-XT includes advanced device controls, ensuring that power consumption does not exceed parameters defined by the user. This includes power budget control functions to limit power output on

devices not reporting correct consumption rates and device priority options to guarantee power to critical devices while avoiding power supply overloads.

Management and Security

The RocketLinx ES7510-XT is equipped with full Layer 2+ management capabilities to provide the most flexible network configuration and control. Features like Link Aggregation Control Protocol allow grouping of multiple ports to enhance bandwidth and provide load balancing while Port-Based VLAN, QoS, IGMP Snooping, and Rate Control features enable optimum control over the network environment. In addition to the full array of management capabilities, the ES7510-XT also supports the most advanced security features to protect the network and guarantee secure, reliable data transmission. Fault relay and e-mail notification of event alarms, DHCP supporting IP and MAC binding, IEEE 802.1X network access control, SSH, and many other controls are included to make secure administration and management a simple task.



connect. communicate. control.

ROCKETLINX SPECIFICATIONS

HARDWARE

Network Interface	
10/100BASE-TX PoE Plus	
10/100/100BASE-TX	
100BASE-FX, 1000BASE-SX/LX/LHX/XD/ZX Gigabit Fiber	
Connector Type	
Eight - RJ45	
Two - RJ45/SFP Combo	
Enclosure	
IP30 Grade Steel Metal Case with Aluminum panel housing for heat dissipation	
Installation Method	
DIN rail	
Wall or panel mount	
LED Indicators	
Power 1/2	
System Status	
Ring Status	
DI and DO Status	
Ethernet Port Link/Activity	
PoE Status	
Gigabit Port Link/Activity	
Digital Input (DI)/Digital Output (DO)	
4-pin screw terminal block with one DI and one DO (Dry Relay Output)	
Serial Console Port	
One RJ45 RS-232 (TXD, RXD, Signal GND), Baud Rate: 9600bps, Data Bits: 8, Parity: None, Stop Bits: 1, Flow Control: None	
Thermal Monitoring	
Embedded board-level thermal detector for main-chip temperature monitoring	
Dimensions	5.0" x 6.3" x 3.7" 12.7 x 16 x 9.4 cm
Product Weight	1.85 lbs 1.29 kg

ETHERNET SPECIFICATIONS

Number of Ports	
Ten: 8 - RJ45 and 2 - RJ45 SFP combo Gigabit uplink	
RJ45	
8 RJ45: 10/100BASE-TX PoE Plus	
2 RJ45: 10/100/1000BASE-TX	
Auto MDI/MDIX, Auto-Negotiation (Speed/Duplex Mode)	
SFP DDM (Optional)	
100BASE-FX Fiber, 1000BASE-SX/LX/LHX/XD/ZX	
Auto-Negotiation (Speed/Duplex Mode)	
Cable Types	
Cat 3, Cat 4, Cat 5, Cat 5e, Cat 6 (UTP or STP)	
Link Distances	
RJ45: 100 meters	
SFP Model	
Port Alarm Relay	Yes
Transfer Packet Size	
64 bytes to 1522 bytes (includes double VLAN tag)	
Standards	
IEEE 802.3af PoE	
IEEE 802.3at LLDP PoE Plus	
IEEE 802.1AB: Link Layer Discovery Protocol (LLDP)	
IEEE 802.1D-2004: Rapid Spanning Tree Protocol (RSTP)	
IEEE 802.1p: Class of Service	
IEEE 802.1Q-2003: VLAN Tagging and GVRP	
IEEE 802.1s: Multiple Spanning Tree Protocol (MSTP)	
IEEE 802.1X: Port based network access control	
IEEE 802.3: 10BASE-T	
IEEE 802.3ab: 1000BASE-TX	
IEEE 802.3ad: Port Trunking with Link Aggregation Control Protocol (LACP)	
IEEE 802.3u: 100BASE-TX Fast Ethernet and 100BASE-FX Fast Ethernet Fiber	
IEEE 802.3x: Flow Control and Back-Pressure	
IEEE 1588-2008: Precision Time Protocol (PTP)	
Internet Protocol	IPv4 and IPv6

PoE FEATURES

PoE Modes	
802.3af	
802.3at (2-event)	
802.3at (LLDP)	
Forced	
Number of PoE Plus Injector Ports	8
PSE Type	
802.3at Type 2	
Alternative A	
Maximum Power/PoE Port (Max.)	
15.4W (IEEE 802.3af)	
30W (IEEE 802.3at)	
Total Power Budget (Max.)	120W at 75°C
Standard PoE Voltage Output	
Yes	
IEEE 802.3af compliant - 47-57VDC	
IEEE 802.3at compliant - 50-57VDC	
PoE Control	
Enable or disable PoE, set/port PoE mode, power	

schedule-based PoE functions	
Power Budget Warning Level	Yes
PoE Powered Device Check	
Real-time status monitoring of PoE PDs with an option to reset the PoE PD	
Real-time PoE Status	Yes
PoE Output Pin-Out (RJ45)	
Pins 1, 2 - V+	
Pins 3, 6 - V-	
PoE Scheduling	
PoE ports are configurable as On/Off by hourly/daily/weekly basis	

MANAGEMENT FEATURES

Configuration and Monitoring	
Out-Band Management: Console Port with Command Line Interface (CLI) - Similar to Cisco CLI, In-Band	
Management: Web	
Interface (HTTP/HTTPS) or a Telnet/SSH console with CLI	
Embedded Watchdog	
Embedded hardware watchdog timer automatically resets system if switch system failure occurs	
System Upgrade/Backup	
Provides TFTP/Web interface for firmware upgrade and configuration backup/restore	
SNMP	
V1, V2c, V3 with SNMP trap function, up to four trap stations	
SNMP MIB	
MIB-II, Bridge MIB, VLAN MIB, IGMP MIB, Ethernet-like MIB, Control Private MIB, and RMON	
Email Warning	
Automatic warning, up to four accounts by pre-defined events	
System Log	
Supports both local mode and server mode	
DHCP	
DHCP client, DHCP server with IP and MAC address binding, Port-based DHCP server configuration and DHCP relay agent (Option 82)	

NETWORK PERFORMANCE

Back-Pressure	
IEEE 802.3x 1000Mbps Half-Duplex only	
Class of Service (CoS)	
IEEE 802.1p 4 priority queues/port	
Flow Control Pause Frame	
IEEE 802.3x 10/100/1000Mbps Full-Duplex	
GMRP	
GARP Multicast Registration Protocol	
IGMP Snooping	
V1/V2/V3 for multicast filtering and IGMP Query V1/V2; Supports unknown multicasting, Processes forwarding policies: drop, flooding, and forward to router port	
IP Security	
Assign authorized IP addresses to specific port, 10 Max/port	
Loop Protection	
Provides Layer 2 loop prevention through the STP, RSTP, and MSTP. Loop protection increases the efficiency of STP, RSTP, and MSTP by preventing ports from moving into a forwarding state that would result in a loop in the network	
Modbus TCP/IP	
CLI support for Modbus TCP/IP communications with Function Code 4 (factory automation). Operates as slave/server device, while a typical master/client device is a host computer running appropriate through Ethernet. The Modbus TCP/IP master can read or write to the Modbus registers provided by the Modbus TCP/IP application software (SCADA/HMI system)	
Packet Buffer Memory	
1Mbits	
Port-Based Network Access Control	
IEEE 802.1X: Supports user authentication by the RADIUS account, password and key for the RADIUS servers (Primary and Secondary), Supports TACACS+	
Port Configuration	
Port Link Speed, Link Mode, Port Status, Enable/Disable	
Port Mirroring	
Online traffic monitoring on multiple selected ports	
Port Security	
Assign authorized MAC addresses to specific port, 10 max/port	
Port Trunk	
IEEE 802.3ad LACP with timer and static port trunk; trunk member up to 8 ports and maximum 5 trunk groups including gigabit Ethernet ports	
Private VLAN	
Direct client ports in isolated/community VLAN to promiscuous port in primary VLAN	
Rate Control	
Ingress filtering for broadcast, multicast, unknown DA or all packets. Egress filtering for all packet types.	
Switch Technology	
32Gbps switch fabric, store/forward switch technology, 8K MAC address	
System Throughput	
8.3 Mega packets/sec	
14,880pps - 10Mbps	
1,488,100pps - 1000Mbps	
Time Synchronization	

Supports IEEE 1588-2008 (PTP) and NTP protocols with daylight savings and localized time sync function	
Prioritization (QoS)	
802.1p CoS tag and IPv4 ToS/DiffServ information to prioritize industrial network traffic	
VLAN	
IEEE 802.1Q tag VLAN with 256 (max) VLAN entries and 2K GVRP entries; 3 VLAN link modes; trunk, hybrid, and link access IEEE 802.1 QinQ supports double VLAN tag function for implementing metro network topologies	

NETWORK REDUNDANCY

Rapid Spanning Tree Protocol	
IEEE 802.1D-2004 Rapid Spanning Tree Protocol (RSTP)	
Compatible with legacy STP and IEEE 802.1w	
Multiple Spanning Tree	
IEEE 802.1s MSTP, each MSTP instance can include one or more VLANs	
Redundant Ring Technology	
Failure recovery within 5ms - Rapid Dual Homing; Multiple uplink paths to upper switches - Ring Trunking; Integrates port aggregate function in ring path to get higher throughput ring architecture - Multiple Ring; Couple or multiples of up to 4 100M rings and up to 2 Gigabit rings in one switch	

ELECTRICAL SPECIFICATIONS

Device Power Input Voltage (DC1/DC2)	
(Positive or Negative)	
802.3af	48VDC (48-57VDC)
802.3at	53VDC (50-57VDC)
Device Power Consumption	
Without PD Load (Max.)	15W
With PD Load (Max.)	140W
Power Connector Type	
One 4-pin terminal block for DC1/2	
Power Input Redundancy	
Dual Redundant Inputs	Passive
PSU Type	
Reverse Polarity Protection	Yes
Digital Output (Relay Output)	
DC Input Voltage	24VDC
Current Consumption (24VDC)	0.5A maximum
Multi-Event Relay Feature	
Power, Port Link, Ring Status Change, Ping, Ping Reset, Dry Output, and DI	

ENVIRONMENTAL SPECIFICATIONS

Air Temperature	
System On	-40° to 75°C
System Off	-40° to 85°C
Operating Humidity (non-condensing)	
0% to 95%	
MTBF	
(Mean time between failures)	50.9 years

EXPORT INFORMATION

Packaged Shipping Weight	4.1 lbs 1.86 kg
Package Dimensions	11.3" x 5.5" x 9.1" 287 x 140 x 231 mm
UPC Code	7-56727-32046-3
ECCN	5A992
Schedule B Number	8517.62.0050

REGULATORY APPROVALS

Emissions	
European Standard EN55022	
AS/NZS CISPR 22	
FCC Part 15 Subpart B	
Class A limit	
Immunity	
European Standard EN55024:	
IEC 1000-4-2/EN61000-4-2: ESD	
IEC 1000-4-3/EN61000-4-3: RF	
IEC 1000-4-4/EN61000-4-4: Fast Transient/ Burst	
IEC 1000-4-5/EN61000-4-5: Surge	
IEC 1000-4-6/EN61000-4-6: Conducted Disturbance	
IEC 1000-4-8/EN61000-4-8: Magnetic Field	
IEC 1000-4-11/EN61000-4-11: DIPS and Voltage Variations	
Safety	
IEC 60950/EN60950 (LISTED)	
CSA C22.2 No. 60950/UL60950 Third edition	
Vibration	IEC 61373
Shock	IEC 61373
Other	
RoHS2 compliant under CE	
NEMA TS2 compliant	
Regulatory Approvals	



Warranty Information

Comtrol offers a 30-day satisfaction guarantee and 5-year limited warranty.

Sales Support

+1.763.957.6000
sales@comtrol.com

Technical Support

+1.763.957.6000
www.comtrol.com/support

Email, FTP, and Web Support

info@comtrol.com
ftp.comtrol.com
www.comtrol.com